

## passive loudspeaker P5 LCR - Surround - Height







## **INTRODUCTION**

The P5 delivers the full dynamic range experience to smaller rooms and rooms with multiple surrounds and height speakers. Its compact cabinet can be oriented either vertically or horizontally, even mounted on the ceiling, thanks to its 80 degree circular waveguide and 1" pro compression driver. The P5 comes in semi-matte black or white finish with a magnetically attached removable grille.

## **TECHNICAL SPECIFICATIONS**

Impedance	8 Ohms nominal Phase Angles less than 45 degrees	Crossover	Asymmetrical, phase aligned 2.2kHz, BSC
Power handling		Components	
continuous	75 Watt	Midrange	5.25" driver with 26mm voice
peak	250 Watt		coil in 5 litre sealed box
Sensitivity		High Frequency	1" compression driver on a
1m/1W	91dB		circular constant directivity
Maximum SPL			wave guide
free standing	107dB continuous, 113dB peak	Connectivity	Gold plated large diameter
in wall	113 dB continuous, 119dB peak		binding posts
Frequency response		Wall Mount	Inserts for VESA 100 bracket and
-3dB points	90Hz and 20kHz		keyholes provided for both vertical
Dispersion pattern			and horizontal mounting
-6dB	Constant directivity; 80° circular from 2.5kHz	Dimensions H x W x D Net weight	304 x 190 x 170mm / 12" x 7.5" x 6.7" 4.8 Kg / 10.6 lbs